

USB SPEAKER TRACKING CAMERA



FEATURES



Implemented with audio positioning and intelligent face detection algorithm.



A tracking camera & an EPTZ 4K full-view camera.



Full-view EPTZ camera can automatically frame all the meeting participants.



Auto switch between close-up image and EPTZ full-view image.



Support HDMI, USB2.0, 3G-SDI & network interface, up to 1080P60 resolution.





Support H.264/H.265/MJPEG video compression.



Support echo cancellation.

DIMENSIONS



DIP Switch HDMI
Ethernet 3G-SDI
Ref.Line in RS-232
Line in DC12V

ACCESSORIES



Wall Bracket

SPECIFICATIONS

Model	KX-VDW200SX
Tracking Camera	
Image Sensor	1/2.8"CMOS, 2MP
Focal	f=3.9mm-46.8mm
Iris	F1.6-F2.8
Zoom	Optical:12X, Digital:12X
FOV	Horizontal72.5°-6.3°
Focus	Auto, Manual, PTZPush, One Push
Shutter Speed	1/1-1/10,000s
AGC	Auto,Manual
White Balance	Auto, Indoor, Outdoor, OnePush, Manual, AutoTrack, Color Temp
Exposure	Auto, Manual, Shutter Priority, IrisPriority
SNRatio	≥50dB
BLC	Yes
Full View Camera	
Image Sensor	1/2.5"4K CMOSSensor, 8.57MP
Lens	2.8mmfocus,4X digitalzoom
FOV	98°
DNR	2D/3D
Video Adjustment	Support EPTZ
PTZ	
Pan	-90°-+90°,0.1°-100°/s
Tilt	-30°-+90°,0.1°-80°/s
Preset Number	64
Network	
Max Image Size	1920×1080@60fps
Video Compression	H.264/H.265/MJPEG
Audio Compression	AAC
Protocol	RTSP, RTMP, RTP, TCP, UDP, ONVIF
Multi-Stream	Support 1xclose-upview, 1xfullview, 1xswitching
Interface	
SDI	1×3G-SDI, VideoFormat: 1080P60/50/30/25, 720P60/50
HDMI	1×HDMI, VideoFormat: SameasSDI
USB	1×USB2.0, supportUVC/UAC
Audio Input	2×3.5mm LINEIN, including one channel echo cancellation reference audio input
Network Interface	1×10M/100M RJ45
General	
Control Protocol	VISCA
Address	1-6
Power Supply	DC12V
Power Consumption	<20W
Working Temperature	0°C-+40°C
Storage Temperature	-20°C-+60°C
Dimension (L×W×H)	245mm×145mm×165mm
Weight	< 2KG